



## Garden Pastel Paint

- for many types of wood outdoors
- quick-drying, durable paint in a vintage look



<b>Application rate</b>	Approx. 1 l/ 13 m <sup>2</sup> . Determine the exact coverage by applying a test coat to the object
<b>Areas of use</b>	<ul style="list-style-type: none"><li>■ <b>Areas of use: Indoors</b></li><li>■ For siding and profiled wood</li><li>■ <b>Areas of use: Outdoors</b></li><li>■ For exterior surfacing, wood houses, roofing boards, summerhouses, carports, pergolas, framework and for restoring existing varnish coatings</li></ul>
<b>Preparation</b>	<ul style="list-style-type: none"><li>■ <b>Substrate requirements</b> The wood must be clean, dry and capable of bearing a load Pressure-impregnated wood must be exposed to weather for at least 2-3 months prior to treatment Wooden components with limited or without dimensional accuracy: maximum wood moisture content 18%.</li><li>■ <b>Substrate preparation</b> Exterior wood must be primed with a wood preservative to protect against blue stain and rot (use wood preservatives safely. Always read the label and product information before use.)</li></ul>
<b>Directions</b>	Set up trial areas to check the compatibility, adhesion and colour on the substrate. Application temperature: +5°C to +25°C Do not use at temperatures below +5°C or in strong sunlight Pre-treat untreated exterior wood with a wood preservative (use wood preservatives safely. Always read the label and product information before use.) Sand grey and weathered wood surfaces down to sound, bright wood. The substrate must be clean, dry and stable
<b>Notes</b>	Not suitable for wooden floors or areas with foot traffic. On planed larch and softwoods with a high resin content, the coating may have reduced adhesion and resistance to weathering. This is especially the case on horizontal year rings, knots and areas of winter growth that are high in resin. Maintenance and renovation must be carried out more frequently on these surfaces. The only remedy for this is pre-weathering or very coarse sanding (P80). If these wood types are rough-sawn, considerably longer maintenance and renovation intervals are to be expected.
<b>Tools / Cleaning</b>	Apply using a brush for water-based stains Clean tools immediately after use with water and detergent
<b>Storage / Shelf life</b>	Store in the sealed original container in a cool, dry, and frost-free place. Can be used for at least 1 year after the date of purchase
<b>Disposal</b>	P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Biocidal Products Regulation</b>	Contains a biocidal product (in-can preservative) with the biocidal agents CMIT/MIT (3:1) for protecting the container content from deterioration by microbial organisms (germs, yeast, etc.). Please note the processing guidelines carefully!
<b>Safety advice</b>	Keep out of the reach of children. Use an A2/P2 combi-filter when spraying. Use a P2 dust filter when grinding or sanding. Ensure the area is thoroughly ventilated during application and drying. Do not eat, drink or smoke while using the paint. In the event of contact with the eyes or skin, rinse out thoroughly and immediately with water. Do not allow it to enter the ground, the sewage system or any bodies of water. Clean tools with soapy water immediately after use. Only send fully emptied containers for recycling. Take any leftover liquid material to the collection point for waste paint.

VOC content as per the  
"Decopaint" Directive  
(2004/42/EC)

EU limit value for the product (cat A/d): max. 130 g/l (2010).  
This product contains < 130 g/l VOC.

---

Precautionary statements /  
Hazard statements  
anthrazit, waldbeere:

Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one and 2-  
methyl-2H-isothiazol-3- one (3:1). May produce an allergic reaction.

---

Precautionary statements /  
Hazard statements  
kreideweiß, lichtgrau,  
himmelblau, jadegrün, petrol,  
pfirsich, elfenbein:

Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one and 2-  
methyl-2H-isothiazol-3- one (3:1). May produce an allergic reaction. Warning! Hazardous respirable  
droplets may be formed when sprayed. Do not breathe spray or mist.