



Facade Paint Plus

- for plaster, masonry, concrete, etc. outdoors
- green growth-repellent, weather-resistant protective paint



Application rate

Ca. 1 l/3 m². Determine the exact coverage by applying a test coat to the object

Areas of use

- For durable coats on outdoor facades
- Suitable for plaster, concrete and masonry (after primer), old dispersion-based paint coats
- Not suitable for old elastomeric paint coats

Property profile

- Weather-resistant facade paint with an anti-algae effect
- Wet abrasion resistance class 3 acc. to DIN EN 13 300 and opacity class 3 acc. to DIN EN 13 300 at 5.5 m² per litre and weather resistance class 2

Directions

Smooth out any cracks, holes or other imperfections using a suitable filler
The substrate must be clean, dry, solid and stable
Remove any stubborn marks properly
Paint over residues with a special insulating and sealing primer
Remove flaking and chalky old coats, lime paint coats or non-adhesive distemper, leaving no residues, and treat with a deep penetrating primer
Pre-treat highly absorbent substrates (usually untreated plaster and concrete surfaces, masonry) with a deep penetrating primer
Thoroughly clean any areas affected by mould and algae, then treat with an algae remover or mould remover (Use biocides with care. Always read the label and product information before use)
Leave new plaster to dry for at least 4 weeks
Do not paint in direct sunlight or on very hot days, because if the paint dries too quickly, visible streaks will appear
Do not use in the rain
Paint continuous areas without taking a break, coating it "wet on wet" as a whole
Drying: Surface dry after approx. 2 hours, can be painted over after approx. 8 hours, completely able to withstand load after approx. 3 days

Notes

Please secure the container against falls and spills during transport.

Tools / Cleaning

Brush, paint roller, airless spraying equipment
Clean the tools immediately after use with warm water

Storage / Shelf life

Store in the sealed original container in a cool, dry, and frost-free place. Can be used for at least 1 year after the date of purchase

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Biocidal Products Regulation

As a "treated product", this product contains a biocidal product (film protection agent) with the active biocidal ingredients octylisothiazolinone and 3-iodo-2-propynylbutylcarbamate to protect the film from infestation by microbial organisms (algae, mildew, etc.). It is essential to observe the processing information!

VOC content as per the "Decopaint" Directive (2004/42/EC)

EU limit value for the product (Cat. A/c): max. 40 g/l (2010).
This product contains < 40 g/l VOC.

Precautionary statements / Hazard statements

warning

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P273 Avoid release to the environment.
- P280L Wear protective gloves/protective clothing/eye protection/face protection.
- P302+P352B IF ON SKIN: Wash with plenty of soap and water.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.



- P501A Dispose of contents/container in accordance with local/regional/national/international regulations.
- H317 May cause an allergic skin reaction.
- H412 Harmful to aquatic life with long lasting effects.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Precautionary statements /
Hazard statements