



Hard Wax Oil

- for wood surfaces in interiors
- impregnating, dirt-repellent protective film

Areas of use	 Areas of use: Indoors For use on wooden flooring and stairs Also for high-quality solid wooden furniture, panelling, skirting boards & cork surfaces We do not recommend using on kitchen worktops due to the constant impact of water
Directions	Laid wooden and cork flooring: 1) Sand using a sanding machine. When doing so, the final sanding should not be finer than P 100–120 2) Then carefully rub the product in using a flat brush Wooden stairs: 1) Sand to a final sanding with 120-grit sandpaper 2) Apply the product using a flat brush and rub in using a white pad 3) Once this is dry, the second coat can be applied Furniture surfaces, smaller wooden objects: 1) Sand with up to 180-grit sandpaper 2) Apply the product using a paintbrush or gauze balls 3) Once this is dry, the second coat can be applied Caution: soaked working materials have a tendency to self-ignite. Allow to dry outdoors on a flame-resistant surface under supervision and fully. Only dispose of fully dried working materials
Tips on use	Risk of self-ignition (DGUV Information 209-046). May not be used at the same workspace as varnishes or stains containing nitrocellulose, collect and dispose of contaminated textiles (e.g. cleaning cloths, work clothes) in fire-resistant waste containers
Tools / Cleaning	Dispose of cleaning residues properly Gauze balls, spreading brushes, paintbrushes Clean the tools with a universal thinner immediately after use
Storage / Shelf life	Store in the sealed original container in a cool, dry, and frost-free place. Can be used for at least 1 year after the date of purchase
Disposal	P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
Safety advice	Keep out of the reach of children. Use an A2/P2 combi-filter when spraying. Use a P2 dust filter when grinding or sanding. Ensure the area is thoroughly ventilated during application and drying. Do not eat, drink or smoke while using the paint. In the event of contact with the eyes or skin, rinse out thoroughly and immediately with water. Do not allow it to enter the ground, the sewage system or any bodies of water. Clean tools with soapy water immediately after use. Only send fully emptied containers for recycling. Take any leftover liquid material to the collection point for waste paint.
Precautionary statements / Hazard statements	Repeated exposure may cause skin dryness or cracking.

Precautionary statements / Hazard statements

BAUFIX Gmbh • www.baufix-online.de 8239 TM-4 08/22 1/1