



## Ultra Topcoat

- for interior walls and ceilings
- high-opacity, breathable interior wall paint



<b>Application rate</b>	Ca. 10 l/70 m <sup>2</sup> . Determine the exact coverage by applying a test coat to the object
<b>Areas of use</b>	<ul style="list-style-type: none"><li>■ <b>Areas of use: Indoors</b></li><li>■ For indoor surfaces such as plaster, gypsum and plasterboard. For ingrain and textured wallpapers</li></ul>
<b>Property profile</b>	<ul style="list-style-type: none"><li>■ Low emission with high degree of coverage</li><li>■ Wet abrasion resistance according to DIN EN 13 300 class 3; equivalent to washproof according to DIN 53 778</li><li>■ Hiding power according to DIN EN 13 300 class 1 at 7.0 m<sup>2</sup>/l - equivalent to 140-150 ml/m<sup>2</sup></li></ul>
<b>Directions</b>	Substrates must be clean, dry, free of grease and capable of supporting a load; remove loose parts Use primer to strengthen sanding and absorbent substrates Suitable for roller or brush application, or airless spraying Surface dry after approx. 2-3 hours, can be painted over after approx. 6 hours
<b>Notes</b>	Please secure the container against falls and spills during transport.
<b>Tools / Cleaning</b>	Brush, paint roller, airless spraying equipment Clean tools immediately after use with water and soap
<b>Storage / Shelf life</b>	Store in the sealed original container in a cool, dry, and frost-free place. Can be used for at least 1 year after the date of purchase
<b>Disposal</b>	P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Safety advice</b>	Keep out of the reach of children. Use an A2/P2 combi-filter when spraying. Use a P2 dust filter when grinding or sanding. Ensure the area is thoroughly ventilated during application and drying. Do not eat, drink or smoke while using the paint. In the event of contact with the eyes or skin, rinse out thoroughly and immediately with water. Do not allow it to enter the ground, the sewage system or any bodies of water. Clean tools with soapy water immediately after use. Only send fully emptied containers for recycling. Take any leftover liquid material to the collection point for waste paint.
<b>VOC content as per the "Decopaint" Directive (2004/42/EC)</b>	EU limit value for the product (Cat. A/a): max. 30 g/l (2010). This product contains < 1 g/l VOC.
<b>Precautionary statements / Hazard statements</b>	Contains 1,2-benzisothiazol-3(2H)-one; 2-methyl-2H-isothiazol-3-one. May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
<b>Precautionary statements / Hazard statements</b>	