



Natural Home Stain

- for interior wood surfaces

- high-quality wax emulsion based on natural resin and linseed oil

Areas of use	For all indoor wood types, e.g. furniture, wall and ceiling panelling
Directions	The substrate must be clean, dry and dust-free. Sand with 150-180 grain sandpaper Permissible wood moisture: 8-12 % Risk of self-ignition (DGUV Information 209-046). May not be used at the same workspace as varnishes or stains containing nitrocellulose, collect and dispose of contaminated textiles (e.g. cleaning cloths, work clothes) in fire-resistant waste containers When applying two coats, sand lightly in between with an abrasive sponge or sandpaper with grit size 240-320 Drying (at +20°C and 65 % rel. humidity): Approx. 12 hours
Tips on use	For priming, dilute with approx. 25% water
Storage / Shelf life	Store in the sealed original container in a cool, dry, and frost-free place. Can be used for at least 1 year after the date of purchase The storage temperature should be between +5 and +35°C
Disposal	P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
Biocidal Products Regulation	Contains a biocidal product (in-can preservative) with the biocidal agents CMIT/MIT (3:1) for protecting the container content from deterioration by microbial organisms (germs, yeast, etc.). Please note the processing guidelines carefully!
VOC content as per the "Decopaint" Directive (2004/42/EC)	EU limit value for the product (Cat. A/e): max. 130 g/l (2010). This product contains < 130 g/l VOC.
Precautionary statements / Hazard statements	Contains reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3- one (3:1) 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Precautionary statements / Hazard statements