



Radiator Varnish

- for iron, steel or cast substrates
- heat-resistant, high-opacity special paint



| | |
|--|---|
| Application rate | Ca. 125 ml/m ² . Determine the exact coverage by applying a test coat to the object |
| Areas of use | ■ For all hot water radiators and other firm substrates indoors |
| Directions | Only use on a cold substrate Substrates must be clean, dry, free of grease and capable of supporting a load; remove loose parts Clean and sand off the old coat Apply 1-2 cover coats depending on the load Drying: dust-dry after approx. 4 hours, can be painted over after approx. 24 hours, only operate the radiator after 3 days have passed Remove any rust, apply an insulating primer beforehand Do not use under 15°C |
| Notes | Please secure the container against falls and spills during transport. |
| Tools / Cleaning | Paintbrush Clean tools immediately after use with water and detergent |
| Storage / Shelf life | Store in the sealed original container in a cool, dry, and frost-free place. Can be used for at least 1 year after the date of purchase |
| Disposal | P501 Dispose of contents/container in accordance with local/regional/national/international regulations. |
| Biocidal Products Regulation | Contains a biocidal product (in-can preservative) with the biocidal agents CMIT/MIT (3:1) for protecting the container content from deterioration by microbial organisms (germs, yeast, etc.). Please note the processing guidelines carefully! |
| Safety advice | Keep out of the reach of children. Use an A2/P2 combi-filter when spraying. Use a P2 dust filter when grinding or sanding. Ensure the area is thoroughly ventilated during application and drying. Do not eat, drink or smoke while using the paint. In the event of contact with the eyes or skin, rinse out thoroughly and immediately with water. Do not allow it to enter the ground, the sewage system or any bodies of water. Clean tools with soapy water immediately after use. Only send fully emptied containers for recycling. Take any leftover liquid material to the collection point for waste paint. |
| VOC content as per the "Decopaint" Directive (2004/42/EC) | EU limit value for the product (cat A/i): max. 140 g/l (2010). This product contains < 140 g/l VOC. |
| Precautionary statements / Hazard statements | Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3- one (3:1). May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. |
| Precautionary statements / Hazard statements | |