



Premium Crystal White Free From Preservatives

- top quality: Opacity class 1 acc. to Din En 13 300 At 7 M² Per litre
- free from preservatives, solvents & plasticisers
- for interior walls & ceilings
- wet abrasion class 2 acc. to DIN EN 13300



Application rate	Ca. 150 ml/m ² . Determine the exact coverage by applying a test coat to the object
Areas of use	■ For mineral substrates (e.g. masonry, concrete, plaster) and construction slabs, wallpaper and old dispersion coatings
Directions	Substrates must be clean, dry, free of grease and capable of supporting a load; remove loose parts Wash off distemper and chalking substrates Use primer to strengthen sanding and absorbent substrates Do not use below +5 °C Wear safety goggles and protective gloves during application Surface dry after approx. 2-3 hours, can be painted over after approx. 6 hours
Notes	Please secure the container against falls and spills during transport. Advice for people who are allergic to isothiazolinone and retention of the technical data sheet under tel. 06221 34210
Tools / Cleaning	Clean the tools immediately after use with warm water and household cleaner, if necessary
Storage / Shelf life	Use up as soon as possible after opening Store in the sealed original container in a cool, dry, and frost-free place. Can be used for at least 1 year after the date of purchase
Disposal	P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
Safety advice	Keep out of the reach of children. Use an A2/P2 combi-filter when spraying. Use a P2 dust filter when grinding or sanding. Ensure the area is thoroughly ventilated during application and drying. Do not eat, drink or smoke while using the paint. In the event of contact with the eyes or skin, rinse out thoroughly and immediately with water. Do not allow it to enter the ground, the sewage system or any bodies of water. Clean tools with soapy water immediately after use. Only send fully emptied containers for recycling. Take any leftover liquid material to the collection point for waste paint.
VOC content as per the "Decopaint" Directive (2004/42/EC)	EU limit value for the product (Cat. A/a): max. 30 g/l (2010). This product contains < 1 g/l VOC.
Precautionary statements / Hazard statements	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Precautionary statements / Hazard statements	