



## Silicone Facade Paint

- the facade remains radiant white for longer, as freshly painted
- extra protection of the paint against algae due to beading effect
- highly water vapour permeable



<b>Application rate</b>	Ca. 150-180 ml/m <sup>2</sup> . Determine the exact coverage by applying a test coat to the object
<b>Areas of use</b>	<ul style="list-style-type: none"><li>■ For durable coats on outdoor facades</li><li>■ Suitable for plaster, concrete and masonry (after primer), old dispersion-based paint coats</li></ul>
<b>Directions</b>	<p>Smooth out any cracks, holes or other imperfections using a suitable filler The substrate must be clean, dry, solid and stable Remove any stubborn marks properly Paint over residues with a special insulating and sealing primer Remove flaking and chalky old coats, lime paint coats or non-adhesive distemper, leaving no residues, and treat with a deep penetrating primer Pre-treat highly absorbent substrates (usually untreated plaster and concrete surfaces, masonry) with a deep penetrating primer Thoroughly clean any areas affected by mould and algae, then treat with an algae remover or mould remover (Use biocides with care. Always read the label and product information before use) Leave new plaster to dry for at least 4 weeks Do not paint in direct sunlight or on very hot days, because if the paint dries too quickly, visible streaks will appear Do not use in the rain Paint continuous areas without taking a break, coating it "wet on wet" as a whole Drying: Surface dry after approx. 2 hours, can be painted over after approx. 8 hours, completely able to withstand load after approx. 3 days</p>
<b>Notes</b>	<p>Please secure the container against falls and spills during transport. Advice for people who are allergic to isothiazolinone and retention of the technical data sheet under tel. 06221 34210</p>
<b>Tools / Cleaning</b>	<p>Clean tools with water immediately after use Brush, paint roller, airless spraying equipment</p>
<b>Storage / Shelf life</b>	<p>Store in the sealed original container in a cool, dry, and frost-free place. Can be used for at least 1 year after the date of purchase</p>
<b>Disposal</b>	<p>P501 Dispose of contents/container in accordance with local/regional/national/international regulations.</p>
<b>Biocidal Products Regulation</b>	<p>Contains as "treated goods" a biocidal product (film preservative) with the biocidal active agent 2-octyl-2H-isothiazol-3-one , 3-iodo-2-propynyl butylcarbamate to protect the film from contamination by microbial organisms (algae, mould etc.). Always follow the directions carefully!</p>
<b>Safety advice</b>	<p>Keep out of the reach of children. Use an A2/P2 combi-filter when spraying. Use a P2 dust filter when grinding or sanding. Ensure the area is thoroughly ventilated during application and drying. Do not eat, drink or smoke while using the paint. In the event of contact with the eyes or skin, rinse out thoroughly and immediately with water. Do not allow it to enter the ground, the sewage system or any bodies of water. Clean tools with soapy water immediately after use. Only send fully emptied containers for recycling. Take any leftover liquid material to the collection point for waste paint.</p>
<b>VOC content as per the "Decopaint" Directive (2004/42/EC)</b>	<p>EU limit value for the product (Cat. A/c): max. 40 g/l (2010). This product contains &lt; 40 g/l VOC.</p>

Precautionary statements /  
Hazard statements



warning

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P273 Avoid release to the environment.
- P280G Wear protective gloves.
- P302+P352A IF ON SKIN: Wash with plenty of water.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P501A Dispose of contents/container in accordance with local/regional/national/international regulations.
- H317 May cause an allergic skin reaction.
- H412 Harmful to aquatic life with long lasting effects.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

---

Precautionary statements /  
Hazard statements