



Anti-Mould Paint

- for areas at high risk of mould
- washable, breathable anti-mould paint



Application rate	Ca. 1 l/7 m ² . Determine the exact coverage by applying a test coat to the object
Areas of use	■ Any walls and ceilings indoors, particularly in rooms with an increased risk of mould (bathroom, kitchen, laundry rooms)
Directions	Before painting, spray any existing mould with a mould remover (use biocidal products with care. Always read the label and product information before use.) and brush off thoroughly once dried Drying (in normal conditions, depending on the characteristics of the substrate): Surface dry after approx. 4-6 hours, can be painted over after approx. 8 hours Do not use below +5 °C
Tips on use	■ Drying Drying (in normal conditions, depending on the characteristics of the substrate): Surface dry after approx. 4-6 hours, can be painted over after approx. 8 hours
Tools / Cleaning	Apply with roller and brush Clean the tools immediately after use with warm water and household cleaner, if necessary
Storage / Shelf life	Store in the sealed original container in a cool, dry, and frost-free place. Can be used for at least 1 year after the date of purchase
First aid measures	If inhaled: Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness bring patient into stable side position for transport. Seek medical treatment in case of complaints. If on skin: Wash immediately with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor. If in eyes: Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor. If swallowed: Do not induce vomiting; call for medical help immediately.
Disposal	P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
Biocidal Products Regulation	Contains as "treated goods" a biocidal product (film preservative) with the biocidal active agent 2-octyl-2H-isothiazol-3-one to protect the film from contamination by microbial organisms (algae, mould etc.). Always follow the directions carefully! Active ingredients: 100 g of this product contain 0,20 g 2-octyl-2H-isothiazol-3-one Use biocides safely. Always read the label and product information before using!
Safety advice	Keep out of the reach of children. Use an A2/P2 combi-filter when spraying. Use a P2 dust filter when grinding or sanding. Ensure the area is thoroughly ventilated during application and drying. Do not eat, drink or smoke while using the paint. In the event of contact with the eyes or skin, rinse out thoroughly and immediately with water. Do not allow it to enter the ground, the sewage system or any bodies of water. Clean tools with soapy water immediately after use. Only send fully emptied containers for recycling. Take any leftover liquid material to the collection point for waste paint.

VOC content as per the
"Decopaint" Directive
(2004/42/EC)

EU limit value for the product (Cat. A/a): max. 30 g/l (2010).
This product contains < 1 g/l VOC.

Precautionary statements /
Hazard statements



warning

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P273 Avoid release to the environment.
- P280L Wear protective gloves/protective clothing/eye protection/face protection.
- P302+P352G IF ON SKIN: Wash with plenty of acid soap and water.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P501A Dispose of contents/container in accordance with local/regional/national/international regulations.
- H317 May cause an allergic skin reaction.
- H412 Harmful to aquatic life with long lasting effects.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Precautionary statements /
Hazard statements